

PRODUCT DESCRIPTION

Our EOS WalkOn rooflight is a fixed roof light suitable for situations that requires pedestrian traffic. The WalkOn uses a 50mm double glazed unit to support a load of up to 500kg per m². An additional silk print for a non-slip surface is an optional extra.



MATERIAL

Our WalkOn rooflight is constructed from glass and aluminium. An insulated timber upstand is included as standard.

GLASS TYPE

EOS WalkOn rooflights are supplied with double glazed super low 'e' coated units with Argon filled cavity. Our standard glass specification is ;

- 50mm double glazed unit.
- 25mm laminated outer pane, 16mm argon filled cavity and 8.8mm clear laminated super Low E inner pane.

U VALUE

Standard:

U-value for the unit overall is 1.06 W/m²K.*

DIMENSIONS, POSSIBILITIES & LIMITATIONS

- 150mm timber upstand.
- 4 standard sizes (non stock):
800mm x 800mm, 1000mm x 1000mm,
1000mm x 1500mm and 1000mm x 2000mm.

WARRANTY

EOS WalkOn rooflights come with a 10 year warranty. Our WalkOn rooflights conform to the most up-to-date regulations and is CE marked according to DS/EN14351-1. CE marking is carried out by the Danish institute of technology and includes the following test: EN1873, DS/EN 717-1, EN/ISO 10077-1 and -2, EN673, DS418, EN12207 and EN1026. Vitral has the ISO9001:2008 certification.

* U-values are calculated according to EN14351 (part of CE standard).

About EOS

EOS is a specialsit division of SKG (London) Ltd, set up with the aim of providing high performance roof glazing direct to market.

EOS are the only stockists of Vitral rooflights in the UK , enabling us to offer a market leading product at competitive prices.

T: 0208 462 3557 E: info@eosrooflights.co.uk
www.eosrooflights.co.uk

Modular Walk On Roof Lights

Standard Sizes (Non-Stock)	To suit structural openings: 800mm x 800mm, 1000mm x 1000mm, 1000mm x 1500mm, 1000mm x 2000mm
Description	Walk on modular glass rooflight(s) with 150mm upstand for easy installation onto flat roofs. Supporting loads up to 500kg per m ² .
Standard	Manufactured to meet the requirements of EN14351-1 (European Regulation for glazing effective since 1st Feb 2010) with declaration of conformity and accompanied by a CE label to prove complete assembly watertightness, thermal transmittance, air permeability and factory production control to ISO 9001.
Installation	Designed for quick and simple installation by any roofing/main contractor. Roof membrane is then dressed around the kerb, framed glass top secured in position with no requirements for silicone sealants.
Impact Safety Standard	Complete unit (glass, frame and kerb) have been tested to CWCT TN66/67 for impact resistance to reduce the likelihood of death or injury caused by falls.
Frame Finish	External aluminium frames polyester powder coated (p.p.c.) to RAL 7043 (70% Gloss) dark grey. Internal EOS kerbs are pre finished white.
Edge Design	Glass surface raised above frame edge to allow water runoff. Glass surface edges have silkscreen print to resist UV degradation of the double glazed unit seals.
Glazing Details	50mm double glazed low emissivity insulating glass units, 25mm laminated outer pane (6mm clear toughened heat strengthened, 1.5mm laminated interlayer, 8mm clear heat toughened heat strengthened float, 1.5mm laminated interlayer, 8mm clear heat toughened heat strengthened float) 16mm agron filled cavity with TGI warm edge spacer, 8.8mm clear laminated low E float glass inner pane.
Thermal Transmittance	U-value 1.06W/m ² K of complete skylight, proven to EN 1873, DS/EN 717-1, EN/ISO 10077-1 and -2, EN 673, DS 418, EN 12207 and EN 1026.
Water Tightness	Watertight to EN 1873.
Air Tightness	Airtight to Class 4 rating 600Pa EN/ISO12207 / EN/ISO1026 (2000).
Sound Insulation	34 (-2, -6) dB sound reduction, tested to EN/ISO717-1/A1.
Upstand Included	150mm upstand included.